



Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]	 <p>Teknomotor S.r.l. Via Argenega 31, I-32038 Quero Vas (BL) www.teknomotor.com</p>
6.0	S1	18000	300	220	21.8	380	12.6	
Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Absorb. Δ [A]	Base voltage Y [V]	Absorb. Y [A]	
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Protection	Ins. Cl.	Part number on nameplate		<p>Peso / weight 13.64 kg</p> <p>Title 5160-D-DBS-P-ER32-HY-RH</p>
6000		24000	400	IP54	F	COM51600398		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		tool type full key	tool type half key	Peso / weight 13.64 kg		Title 5160-D-DBS-P-ER32-HY-RH
rev. n°	description			date	signature	Customer	Drawing code	
01	Sostituito cuscinetto posteriore da 6202 a 6203			14/12/2017	D. Bottarel	Catalogo	COM51600398	
00	Emissione			09/12/2016	D. Bottarel	Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5 mm Rugosità secondo UNI ISO 1302		
drawn - date	approved - date	checked - date	sostituisce il			foglio / sheet	scala	
D. Bottarel - 14/12/2017	S. Perli - 14/12/2017	S. Perli - 14/12/2017	sostituito dal			1 / 1	n.d.	