



Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.	TEKNOMOTOR
5.6	S1	18000	300	220	380	IP54	F	
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate		
6000		24000	400	20.0	11.5	COM51600454		
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		tool type full key	tool type half key	Peso / weight		
						14.74 kg		
Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$	Title
								5160-D-2DB-P-ER32-HY-RH
rev. n°	description			date	signature	Customer		
00	Emissione			12/04/2019	D. Bottarel	Catalogo		
						Drawing code		
						COM51600454		
drawn - date	approved - date	checked - date	sostituisce il		foglio / sheet	scala	A4	
D. Bottarel - 12/04/2019	S. Perli - 12/04/2019	S. Perli - 12/04/2019	sostituito dal		1 / 1	n.d.		